



also available
with collar



Anchor SF

The Traditional Fixing for solid bases

Features and Applications

- For all kind solid materials: concrete, natural stone, solid brick;
- Should be used wood-, chipboard- and self-tapping screws;
- The anti-rotation lock prevents the plug rotation in the drill hole;
- High-quality polyamide (nylon) ensures resistance to weathering and ageing, corrosion and rotting;
- Withstands temperatures from -40 °C to +80 °C;
- Possibility to direct the expansion forces to let them run parallel to the edge of the building material.

Installation



Drill



Insert Fixing



Turn the screw



Result in solid brick



The required screw length = plug length + Fixture thickness + 1x screw diameter.

Always observe the screw diameter stated in our recommendation.



TECHNICAL DATA

Ø Anchor (mm)	SF 5	SF 6	SF 7	SF 8	SF 10	SF 12
Anchor length (mm)	25	30	30	40	50	60
Ø Screw (mm)	2,8 3,8	3,5 4,8	4,2 5,5	4,5 6,1	6,0 8,0	8,0 10,0
* LOAD SAFE Kgf	28	40	50	66	120	180

Concrete

Nylon Anchor SF with wood-screw



PACKING



Na hora de **fixar**  **Acerte na bucha**

For further information: www.sfor.com.br